

* SOLIDPRO (MTP)

SIZE	RIM	EasyFit (Clip)	O.D mm	W.D mm	Load Capacity(kg)						Weight kg
					Forklift Truck		Others			Static 0km/h	
					Load	Steer	~6km/h	~10km/h	~25km/h		
4 inch											
3.00 - 4	2.10	o	252	85	260	195	260	235	195	295	3.5
4.00 - 4	2.50C	o	306	105	535	412	535	485	412	620	7.0
5 inch											
3.50 - 5	2.50C	o	293	99	540	420	540	500	420	605	5.7
	3.00SP	o	293	99	540	420	540	500	420	605	6.0
8 inch											
4.00 - 8	3.00D	o	405	116	950	730	950	860	730	1100	11.1
	3.75I	o	405	116	950	730	950	860	730	1100	11.4
5.00 - 8	3.00D	o	458	125	1415	1090	1415	1285	1090	1645	16.1
	3.25I	o	458	125	1415	1090	1415	1285	1090	1645	16.4
	3.75I	o	458	125	1415	1090	1415	1285	1090	1645	16.4
15 X 4 1/2 - 8 (125 / 75 - 8)	3.00D	o	376	115	1040	800	1040	945	800	1210	9.7
	3.25I	o	376	115	1040	800	1040	945	800	1210	11.4
16 X 6 - 8 (150 / 75 - 8)	4.33R	o	419	152	1495	1150	1495	1360	1150	1740	16.2
18 X 7 - 8 (180 / 70 - 8)	4.33R	o	454	156	2145	1650	2145	1945	1650	2490	20.5
18 X 9 - 8	7.00E	o	462	208	2300	1900	2300	2090	1900	2945	30.5
9 inch											
15 X 5 1/2 - 9	4.00E	o	384	131	1170	900	1170	1060	900	1360	10.3
6.00 - 9	4.00E	o	530	139	1885	1450	1885	1710	1450	2190	26.5
21 X 8 - 9	6.00E	o	518	184	2755	2120	2755	2500	2120	3200	33.0
10 inch											
180 / 60 - 10	5.00F	o	462	162	2410	1850	2410	2180	1850	2795	20.1
200 / 50 - 10	6.50F	o	457	198	2470	1900	2470	2240	1900	2870	24.9
6.50 - 10	5.00F	o	547	172	2340	1800	2340	2125	1800	2720	35.8
	5.50F	o	547	172	2340	1800	2340	2125	1800	2720	36.0
23 X 9 - 10 (225 / 75 - 10)	6.50F	o	583	204	3445	2650	3445	3125	2650	4000	46.9
7.50 - 10	5.00F	o	630	192	3070	2360	3070	2785	2360	3565	51.6
	5.50F	o	630	192	3070	2360	3070	2785	2360	3565	51.9
12 inch											
23 X 10 - 12 (250 / 60 - 12)	8.00G	o	589	240	3770	2900	3770	3420	2900	4380	52.9
315 / 45 - 12	10.00G	o	574	285	4485	3450	4485	4070	3450	5210	56.1
27 X 10 - 12 (250 / 75 - 12)	8.00G	o	676	246	3900	3000	3900	3540	3000	4530	74.6
7.00 - 12	5.00S	o	653	172	2920	2240	2920	2645	2240	3380	46.4
13 inch											
23 X 5 (150 / 100 - 13)	3.75P	o	622	140	1495	1150	1495	1360	1150	1735	32.3
15 inch											
8.15 - 15 (28 X 9 - 15, 225 / 75 - 15)	7.00	o	696	212	3445	2650	3445	3125	2650	4380	60.0
28 X 12.5 - 15 (355 / 45 - 15)	9.75	o	711	310	5525	4250	5525	5015	4250	6420	92.0
32 X 12.1 - 15	9.75	o	818	299	6500	5000	6500	5900	5000	9060	119.9
355 / 65 - 15	9.75	o	822	300	7800	6000	7085	6430	5450	9060	133.8
250 - 15 (250 / 70 - 15)	7.00	o	716	226	4745	3650	4745	4310	3650	5510	67.6
	7.50	o	716	226	4745	3650	4745	4310	3650	5510	68.1
300 - 15 (315 / 70 - 15)	8.00	o	820	266	5850	4500	5850	5310	4500	6795	111.3
6.00 - 15	4.50E	o	693	155	2455	1820	2455	2095	1820	3165	44.0
7.00 - 15	5.50	o	734	175	3545	2725	3545	3215	2725	4115	56.5
	6.00	o	734	175	3545	2725	3545	3215	2725	4115	56.8
7.50 - 15	5.50	o	755	197	3900	3000	3900	3540	3000	4530	67.3
	6.00	o	755	197	3900	3000	3900	3540	3000	4530	68.0
	6.50	o	755	197	3900	3000	3900	3540	3000	4530	69.2
8.25 - 15	5.50	o	807	202	4615	3550	4615	4190	3550	5510	81.5
	6.50	o	807	202	4750	3650	4750	4300	3650	5510	82.3
400 / 60 - 15	11.00	o	817	332	8970	6900	8970	8140	6900	10350	144.2
16 inch											
7.50 - 16	5.50	o	780	197	3950	3050	3950	3600	3050	4605	70.9
	6.00GS	o	780	197	3950	3050	3950	3600	3050	4605	73.1
8.00 - 16	5.50	-	807	207	4180	3190	4180	3800	3190	4785	83.6
20 inch											
6.50	-	-	1006	232	5400	4500	5400	4905	4500	6795	142.0
9.00 - 20	7.00	-	1006	232	5400	4500	5400	4905	4500	6795	142.5
	7.50	-	1006	232	5400	4500	5400	4905	4500	6795	143.1
	8.00	-	1006	232	5400	4500	5400	4905	4500	6795	143.9
10.00 - 20	7.00	-	1024	258	6000	5000	6000	5450	5000	7550	162.1
	7.50V	-	1024	258	6000	5000	6000	5450	5000	7550	162.6
	8.00V	-	1024	258	6000	5000	6000	5450	5000	7550	163.5
11.00 - 20	7.50V	-	1090	280	6540	5450	6540	5940	5450	8230	199.2
	8.00V	-	1090	280	6540	5450	6540	5940	5450	8230	200.2
12.00 - 20	8.00V	-	1092	297	7560	6300	7560	6865	6300	9440	217.3
	8.50	-	1092	297	7560	6300	7560	6865	6300	9440	219.1
	10.00W	-	1092	297	7800	6500	7800	7085	6500	9770	224.9
24 inch											
8.00V	-	-	1193	297	8040	6700	8040	7305	6700	10040	247.5
12.00 - 24	8.50	-	1193	297	8040	6700	8040	7305	6700	10040	248.9
	10.00W	-	1193	297	9000	7500	8500	7750	7100	10040	258.4
14.00 - 24	10.00W	-	1313	322	11100	9250	11100	10085	9250	13855	353.2

※ Load Capacity: Counter Balanced Forklift Truck, up to 25 km/h