

\* ALL-PRO HP (CBX)

Size	RIM	EasyFit (Clip)	O.D	W.D	Load Capacity(kg)	
			mm	mm	Forklift Truck	
					Load	Steer
<b>8 inch</b>						
5.00 - 8	3.00D	o	458	125	1415	1090
15 X 4 1/2 - 8 (125/75-8)	3.00D	o	376	115	1040	800
16 X 6 - 8 (150/75-8)	4.33RW	o	419	152	1495	1150
18 X 7 - 8 (180 / 70 - 8)	4.33RW	o	454	156	2145	1650
<b>9 inch</b>						
15 X 5 1/2 - 9 (140/55-9)	4.00E	o	384	131	1170	900
6.00 - 9	4.00E	o	530	139	1885	1450
21 X 8 - 9 (200 / 75 - 9)	6.00E	o	518	184	2755	2120
<b>10 inch</b>						
6.50 - 10	5.00F	o	547	172	2340	1800
23 X 9 -10 (225 / 75 - 10)	6.50E	o	583	204	3445	2650
200 / 50 -10	6.50F	o	457	198	2470	1900
<b>12 inch</b>						
7.00 - 12	5.00S	o	653	172	2920	2240
23 X 10 - 12 (250 / 60 - 12)	8.00G	o	589	240	3770	2900
27 X 10 - 12 (250/75-12)	8.00G	o	676	246	3900	3000
<b>15 inch</b>						
7.00 - 15	5.50	o	734	175	3545	2725
7.50 - 15	6.50	o	755	197	3900	3000
8.15 - 15 (28 X 9 - 15, 225 / 75 - 15)	7.00	o	696	212	3445	2650
250 - 15 (250/70-15)	7.00	o	716	226	4745	3650
250 - 15 (250/70-15)	7.50	o	716	226	4745	3650
300 - 15 (315/70-15)	8.00	o	812	266	5850	4500
8.25 - 15	6.50	o	807	202	4750	3650
28 X 12.5 - 15 (355/45-15)	9.75	o	711	310	5525	4250
32 X 12.1 - 15	9.75	o	807	299	6500	5000
355 / 65 - 15	9.75	o	822	300	7800	6000

\* Load Capacity: Counter Balanced Forklift Truck, up to 25 km/h