

\* NEXEN

SIZE	LUG	CB	MS	PL	RIB	RIM	EasyFit (Clip)	O.D mm	W.D mm	Load Capacity(kg)					Weight kg	
										Forklift Truck		Others				Static 0km/h
										Load	Steer	~6km/h	~10km/h	~25km/h		
<b>4 inch</b>																
3.00 - 4					o	2.50C	o	250	85	260	195	260	235	195	295	3.3
<b>5 inch</b>																
3.50 - 5		o				2.50C	o	293	99	540	420	540	500	420	630	5.5
<b>8 inch</b>																
2.00 - 8 (100/50-8)					o	2.50C	o	305	98	825	635	825	750	635	955	4.4
3.00 - 8					o	2.50C	o	358	102	875	675	875	800	675	1015	8.2
4.00 - 8		o			o	3.00D	o	405	116	950	730	950	860	730	1100	11.2
4.00 - 8		o			o	3.75I	o	405	116	950	730	950	860	730	1100	12.3
5.00 - 8					o	3.75I	o	458	125	1415	1090	1415	1285	1090	1645	18.0
<b>9 inch</b>																
6.00 - 9					o	4.00E	o	530	139	1885	1450	1885	1710	1450	2190	27.4
6.00 - 9					o	4.00EK	o	535	140	1885	1450	1885	1710	1450	2190	26.5
<b>12 inch</b>																
23 X 10 - 12 (250 / 60 - 12)		o				8.00G	o	589	240	3770	2900	3770	3420	2900	4380	49.8
7.00 - 12					o	5.00S	o	653	172	2920	2240	2920	2645	2240	3380	48.3
<b>15 inch</b>																
7.00 - 15		o				5.50	o	734	175	3545	2725	3545	3215	2725	4115	54.7
<b>16 inch</b>																
6.50 - 16					o	5.50F	-	742	177	2600	2000	2600	2360	2000	3000	55.5
8.00 - 16					o	5.50	-	807	207	4180	3190	4180	3800	3190	4785	80.4
9.00 - 16		o			o	5.50	-	852	232	4430	3405	4430	4010	3405	5110	104.5
9.00 - 16		o			o	6.50	-	852	232	5240	4030	5240	4745	4030	6045	105.0
<b>20 inch</b>																
8.25 - 20		o			o	6.00	-	955	222	4380	3650	4380	3980	3650	5550	117.3
8.25 - 20		o			o	6.50	-	955	222	4380	3650	4380	3980	3650	5550	119.1
8.25 - 20		o			o	7.00T	-	955	222	4380	3650	4380	3980	3650	5550	119.5
9.00 - 20		o				6.50	-	1006	232	5400	4500	5400	4905	4500	6795	140.9
9.00 - 20		o				7.00	-	1006	232	5400	4500	5400	4905	4500	6795	140.7
9.00 - 20		o				8.00	-	1006	232	5400	4500	5400	4905	4500	6795	140.9
10.00 - 20		o				7.50V	-	1024	258	6000	5000	6000	5450	5000	7550	160.3
10.00 - 20		o				8.00V	-	1024	258	6000	5000	6000	5450	5000	7550	161.5
12.00 - 20					o o	8.00V	-	1092	297	7560	6300	7560	6865	6300	9440	229.4
12.00 - 20					o o	8.50	-	1092	297	7560	6300	7560	6865	6300	9440	231.6
12.00 - 20					o o	10.00W	-	1092	297	7800	6500	7800	7085	6500	9770	233.8

\* Load Capacity: Counter Balanced Forklift Truck, up to 25 km/h